

Smart Waste Segregation and Recycling System: A Systematic Literature Review and System Design

Nandini K N¹, Amrutha S N², Harivignesh V S², Namrutha B²

¹Assistant Professor, Department of ISE, Sri Sairam College of Engineering, Anekal, Bangalore

²Final Year, BE (ISE), Sri Sairam College of Engineering, Anekal, Bangalore

DOI: doi.org/10.34293/iejcsa.v4i5.174

Abstract—Municipal solid waste management is the point at which decades of production and consumption converge into a single operational problem, and how well that convergence is handled has a direct bearing on public health, landfill life, and the share of recoverable material that is actually recycled rather than discarded. For decades this convergence point has been managed through manual segregation—first by residents at the point of disposal, and again by sanitation workers at collection and material-recovery facilities—an approach that is labor-intensive, physically hazardous, inconsistent across households and shifts, and structurally reactive, since contamination in a waste stream is usually discovered only after different waste types have already been commingled. This review surveys eight recent works spanning computer-vision and deep-learning waste classification, sensor-driven smart-bin segregation hardware, fill-level monitoring with collection-route optimization, and gamified citizen-engagement applications for recycling behavior. Read together, these works show a consistent shift away from purely manual, end-of-pipe sorting and toward continuous, automated, and increasingly behavior-aware waste management. At the same time, nearly every reviewed approach treats bin-level segregation, collection logistics, and citizen behavior as separate problems, and only one line of work attempts to close the loop between automated hardware and the resident whose sorting habits determine how much contamination ever reaches a bin in the first place. Building on these findings, this paper presents the design of an Intelligent Smart Waste Segregation and Recycling System: a three-tier, sensor-plus-software platform that combines an edge-deployed computer-vision classification module for real-time, bin-level sorting into biodegradable, recyclable, and hazardous streams; a cloud analytics layer that performs fill-level prediction, data-quality validation, and dynamic collection-route optimization; and a citizen-facing mobile application that closes the loop through gamified recycling rewards and a live, color-coded municipal dashboard. The resulting architecture is intended to move municipal waste operations away from reactive, labor-bound sorting and toward continuous, evidence-based, and behaviorally reinforced recycling.

Index Terms—Smart waste management, computer vision, waste classification, deep learning, IoT sensors, smart bins, recycling, route optimization, gamification, circular economy.

INTRODUCTION

The collection and segregation of municipal solid waste is shaped by a constraint that most other logistics problems do not face: the value of the material being handled depends entirely on how cleanly it is separated before it is compacted, transported, and commingled with everything else in a truck or landfill cell. In conventional municipal

settings, that separation still depends mainly on two manual steps—a resident sorting waste into the correct bin at home, and a sanitation worker re-sorting whatever the resident got wrong at a collection point or material-recovery facility. This works, up to a point, but it is slow, inconsistent, and, critically, reactive. Contamination is usually discovered only once recyclable material has already been mixed with organic or hazardous waste, by which point an entire batch may be redirected to a landfill rather than a recycling stream. Compounding this, the volume and composition of waste generated by a city block or a household is volatile and difficult to predict from fixed collection schedules alone, so overflowing bins and half-empty collection runs tend to occur side by side within the same route.

A parallel shift is underway in how citizens are expected to participate in this process. Rather than relying purely on printed sorting guidelines and civic goodwill, newer platforms increasingly treat the resident as an active, incentivized participant—rewarding correct sorting through points, leaderboards, and redeemable prizes so that recycling becomes a habit reinforced by immediate feedback rather than an abstract civic duty. This review draws on eight recent works spanning both the segregation side of this problem (computer-vision classification, sensor-driven bin hardware, and fill-level-aware route optimization) and the behavioral side (gamified citizen-engagement applications), in order to ground the design of an Intelligent Smart Waste Segregation and Recycling System capable of addressing both dimensions at once.

It is worth noting that these two sides of the problem have historically been treated as separate research tracks. Segregation-hardware work tends to focus on what happens once waste reaches a bin—how it is sensed, classified, and physically sorted—while citizen-engagement work focuses on what happens before that, in the moment a resident decides whether to bother sorting at all. Few of the works reviewed attempt to connect the two, even though the contamination a smart bin has to correct for is, in large part, a downstream consequence of a sorting decision a gamified application could have influenced upstream. Recognizing this connection is part of the motivation for treating citizen-engagement literature as directly relevant background for a segregation-hardware platform, rather than as an unrelated adjacent field.

The environmental and economic stakes of getting this right are not trivial. Recyclable material carries value only while it remains uncontaminated, because a single wet, organic, or hazardous item mixed into an otherwise clean batch of plastic or paper can be enough to disqualify the entire batch from recycling and send it to landfill instead. A municipality operating on manual inspection alone effectively accepts certain baseline rate of misdirected recyclables as a cost of doing business, since no sanitation crew, however diligent, can re-sort every bin on every route with perfect consistency. Even a modest improvement in how early a contamination event is detected and corrected—ideally at the point of disposal rather than at a material-recovery facility—can meaningfully change how much collected waste is actually recycled rather than landfilled.

This review is organized to build toward a specific design outcome rather than to catalogue the field for its own sake. Section II lays out the operational and technical background shared across the reviewed systems. Section III explains how the corpus was assembled and evaluated. Section IV works through the eight reviewed sources by theme. Section V compares them directly along several axes. Section VI distills the resulting gaps, and Sections VII through IX use those gaps to justify and describe the architecture of the proposed Intelligent Smart Waste Segregation and Recycling System, closing with its system requirements and overall conclusions.

A. Objectives of This Review

This review pursues four goals. First, to organize the reviewed approaches by their primary design emphasis—computer-vision classification, sensor-driven segregation hardware, fill-level monitoring and route optimization, or citizen-behavior gamification. Second, to compare the advantages and structural limitations reported for each approach. Third, to identify the gaps that most directly constrain a deployable, city-scale segregation and recycling platform. Fourth, to translate those gaps into concrete architectural decisions for the proposed Intelligent Smart Waste Segregation and Recycling System.

B. Background

Technical Evolution of Smart Waste Segregation

The approaches reviewed here fall loosely into three generations. The earliest generation instruments a conventional bin with basic sensors—typically an ultrasonic sensor for fill level and a moisture sensor to distinguish wet from dry waste—while leaving the actual sorting decision to whichever mechanical gate the sensor readings trigger. A second generation introduces computer vision and deep-learning classification directly at the bin or on a short conveyor, so that individual items can be recognized and routed into the correct compartment rather than relying on a single moisture or proximity reading. The most recent generation, which this review emphasizes, layers real-time fill-level telemetry, predictive route optimization, and—increasingly—gamified citizen-facing applications on top of that classification core, so that segregation accuracy, collection efficiency, and resident behavior are treated as parts of the same feedback loop rather than three separate problems.

Motivation for Combining Segregation Hardware with Logistics and Citizen Behavior

Although bin-level classification hardware, collection-route optimization, and citizen-engagement applications are usually studied separately, they share a common underlying object: a stream of material whose recyclable value depends on decisions made by different actors at different points in time. A gamified application that gets a resident to sort correctly is, in effect, preventing a contamination event that a downstream classification bin would otherwise have to detect and correct for; a route-optimization system that collects a bin before it overflows is preventing exactly the kind of overspill mixing that a well-sorted bin

would otherwise be undone by. Bringing insight from citizen-engagement and logistics literature into the design of a segregation-hardware platform—even without directly integrating all three systems from the outset—helps clarify which stage of the waste stream is most cost-effective to correct, and reinforces the case for treating behavior, hardware, and logistics as one coupled design problem rather than three independent ones.

The Resident and Sanitation Worker as Central End Users

A theme that runs through the more recent works in this corpus, and that shapes the proposed system's design directly, is a shift in who the software is actually built for. Earlier tools in this space were largely built for a technically literate municipal administrator—someone comfortable configuring sensor thresholds, reading a table of bin-level statistics, or setting up a routing algorithm's parameters. The two people who most directly determine whether a waste stream stays clean, however, are rarely that administrator: the resident, whose day-to-day sorting habits determine how much contamination ever reaches a bin, and the sanitation worker, whose route and safety depend on whether that bin's contents match what the truck is prepared to handle. Designing for these two end users as the primary audience—rather than as a secondary audience for a system originally built with a technical administrator in mind—has direct architectural consequences, favoring a simple, reward-driven mobile experience for residents, a live operational map for sanitation dispatchers, and automated on-bin correction rather than a configuration-heavy back office, all of which are reflected in the system proposed in Section VII.

LITERATURE REVIEW

Review Methodology

A. Corpus and Search Scope

Eight studies addressing computer-vision and deep-learning waste classification, sensor-driven smart-bin segregation hardware, IoT-based fill-level monitoring, collection-route optimization, and gamified citizen-engagement applications for recycling were selected for detailed review. Each was assessed for its stated architecture, its reported advantages, and the limitations the original authors themselves acknowledged.

B. Inclusion Criteria

A source was included if its primary focus was an automated or semi-automated approach to classifying, sorting, monitoring, collecting, or behaviorally encouraging the correct segregation of household or municipal waste, or a closely related citizen-facing application with a directly transferable architecture (e.g., a gamified recycling-reward platform).

C. Extraction Framework

For each source, four fields were extracted: (i) the core technical approach; (ii) its principal operational advantages; (iii) its acknowledged disadvantages or limitations; and (iv)

how directly its architecture maps onto the design of a city-scale, sensor-and-software segregation platform.

D. Literature Review: Thematic Synthesis

The eight sources reviewed fall into four thematic groups: computer-vision and deep-learning waste classification; sensor-driven smart-bin segregation hardware; fill-level monitoring and collection-route optimization; and citizen engagement through gamification. Reading across these groups rather than treating each source in isolation makes it easier to see where the underlying capabilities overlap, where they are redundant, and—more importantly—where a real deployment would need to combine two or more of them to be genuinely useful to a municipality and its residents.

E. Computer-Vision and Deep-Learning Waste Classification Approaches

The AI-powered Waste Sorting Apparatus (AI-WSA) described in [1] integrates deep learning with electromechanical sorting to automate the segregation of plastic, paper, and metal waste, evaluating three pre-trained architectures—NASNet-Mobile, EfficientNet-B0, and MobileNetV3-Large—on an edge GPU. Its principal strength is that it demonstrates genuine edge-AI feasibility: EfficientNet-B0 achieved the highest classification accuracy, while MobileNetV3-Large delivered the best throughput with only a small accuracy trade-off, and the full system operated within a compact, low-power envelope suitable for a real bin installation. Its central weakness, acknowledged by the authors' own analysis, is a persistent difficulty classifying plastic items correctly even after transfer learning, since plastic packaging varies far more in shape, color, and translucency than paper or metal.

A related classification approach in [2] pairs computer vision and deep learning with an IoT layer capable of segregating municipal waste into Organic and Recyclable categories, with the explicit goal of eliminating the health risk manual segregation poses to municipal workers by removing them from direct contact with unsorted waste. This model demonstrates that a two-class split is achievable with modest hardware, and its IoT layer allows classification events to be logged centrally, but a coarse organic/recyclable split leaves the harder problem—distinguishing plastic, paper, metal, and glass from one another—entirely unaddressed, and the work offers no discussion of how the system behaves when items are occluded or partially visible on approach.

A broader survey in [3] undertakes a comprehensive analysis of smart-dustbin systems built on IoT and deep learning, tracing the evolution of bin design and cataloguing the datasets, sensing modalities, and classification techniques used across the field. Its contribution is foundational rather than applied: it maps out which design choices recur across prior smart-bin research and explicitly highlights gaps left uncovered by that research, but it does not itself propose or validate a deployable end-to-end architecture, nor does it address how a classification model's accuracy degrades once deployed against real, messy, mixed household waste rather than a curated benchmark dataset.

F. Sensor-Driven Smart-Bin Segregation Hardware

A sensor-based smart waste segregation and management device described in [4] detects waste using an ultrasonic sensor for presence and fill level and a moisture sensor to distinguish wet from dry waste, with a microcontroller relaying the resulting classification to a cloud database over IoT. This design considerably lowers the cost and complexity of a first-generation smart bin and gives a municipality centralized, near-real-time visibility into bin status without requiring a camera or a trained model. Its central weakness, however, is one the broader literature explicitly calls out: a moisture sensor cannot distinguish a genuinely wet organic item from a dry or metal item that happens to carry residual water droplets.

A more capable smart bin described in [5] pairs deep learning with IoT connectivity to segregate waste as biodegradable or non-biodegradable, reporting a high average classification accuracy for real-time waste objects without human intervention. This considerably improves on purely moisture- or proximity-based sensing and demonstrates that a deep-learning classifier can run reliably at the bin itself rather than only in a cloud backend. Its scope, however, is limited to a binary bio/non-bio split, and like [4] it depends on stable lighting and a relatively unobstructed view of each item, conditions that are difficult to guarantee at every bin location a city might deploy across a range of outdoor and indoor settings.

G. Platform Scalability, Fill-Level Monitoring, and Route Optimization

A logistics-focused approach in [6] integrates IoT-based smart-bin allocation with a central monitoring system and an enhanced vehicle-routing algorithm, using an ultrasonic-sensor-derived fill level in conjunction with a time-dependent penalty concept and a variable neighborhood search with ant-colony optimization to schedule collection dynamically rather than on a fixed calendar. This work directly addresses the operational side of the problem that classification-focused works largely ignore, and its case-study validation shows the routing algorithm outperforming simpler heuristic baselines. Its routing model, however, is built around historical and current fill-level data rather than any signal about what is actually inside a bin, so a bin that is full of correctly sorted recyclables and a bin that is full of contaminated mixed waste are, from the router's perspective, indistinguishable and equally prioritized.

A two-phase platform described in [7], termed an intelligent and smart solid waste management system (iSSWMs), combines a first phase in which IoT-connected smart bins alert a cloud server and a mobile application once capacity is reached, with a second phase in which a deep-learning model sorts plastic, glass, and metal along a conveyor with very high reported training accuracy. This is the reviewed work that comes closest to combining fill-level logistics and classification within a single architecture, and its two-phase separation of collection alerting from material sorting is a sensible division of labor. Its conveyor-based sorting stage, however, is designed for a centralized facility rather than a distributed, bin-level deployment, meaning the classification intelligence is applied only after waste has

already been collected and commingled in transit, rather than at the point of disposal where contamination could have been prevented in the first place.

H. Citizen Engagement and Gamification

A gamified mobile application described in [8], developed under an EU-funded sustainability project, rewards users with points for scanning QR codes located on waste bins and for sharing sustainability-related content on social media, with points redeemable for prizes offered by local sponsors. Evaluated through a survey-based model of adoption intention, the study found that a user's expected social benefit and perceived risk were the strongest predictors of willingness to adopt the application, and—notably—that perceived risk reduced how useful users judged the app to be without actually driving them away from using it. This is the only reviewed work that treats the resident's sorting decision itself as the object of the intervention, but the application has no mechanism to verify that a scanned bin was actually used correctly, nor any connection to the sensor or classification layer that a smart bin at the same location might already have.

Two clear axes separate the reviewed works. The first is classification depth: [1], [2], and [5] attempt genuine multi- or binary-class recognition of what an item actually is, while [4] infers waste type indirectly from a single physical property such as moisture. The second is operational integration: only [7] connects bin-level alerting to a downstream sorting stage within one architecture, and only [6] closes the loop into an automatic logistics action—a routing decision—rather than stopping at a sensor reading. No single reviewed system combines accurate bin-level classification, contamination-aware routing, and citizen behavioral engagement within one architecture—each capability so far has been demonstrated in isolation.

decision. [1], [2], [4], and [5] intervene at the bin itself, after the resident's decision has already been made but before collection.

[6] and [7] intervene after collection, at the routing and facility level. This suggests that accessibility to, and influence over, the resident's original sorting decision—rather than sorting accuracy alone—may be the more overlooked lever separating the current body of segregation research from a genuinely low-contamination waste stream, since every downstream correction carries a cost in labor, energy, or lost recyclable value that an upstream behavioral nudge would have avoided entirely.

A fourth pattern worth noting is that classification sophistication and operational scope tend to move in opposite directions. The systems with the most advanced per-item classification—[1] and [5]—are demonstrated at a single bin or apparatus and say little about how that intelligence would coordinate across a city's worth of bins, whereas the systems that reach furthest into city-scale operations—[6] and [7]—either ignore what is inside a bin altogether or move the classification step downstream to a centralized facility. No reviewed system manages to combine strong per-item classification with both

distributed, bin-level deployment and city-scale logistics coordination at the same time, which is precisely the combination a practical, municipal-scale segregation platform would need to strike.

Taken as a whole, this comparison suggests that the field has developed strong, individually validated components—edge-deployable classification, sensor-driven bin hardware, contamination-blind route optimization, and citizen gamification—without yet producing an architecture that assembles them behind a single feedback loop that runs from resident behavior through bin-level correction to collection logistics. This is less a criticism of any individual reviewed work, each of which addresses its own stated problem well, than an observation about the corpus as a whole: the next meaningful advance in smart waste segregation is more likely to come from integration than from further improving any one component in isolation.

RESEARCH GAP

Five gaps recur across the reviewed literature, in rough order of how foundational they are. Taken individually, each gap looks like a manageable engineering limitation; taken together, they describe a field where per-item classification accuracy has matured faster than the sensing safeguards, integrated logistics, and behavioral feedback loops needed to put that accuracy to work across an entire city.

- **Sensor and classification fragility.** Approaches that rely on a single sensing modality—most explicitly the moisture sensing in [4]—have no described mechanism for cross-checking a reading before it is acted on, so a dry item with residual water droplets or a wet item resting on a dry surface is misclassified with no fallback. Vision-based approaches such as [1], [2], and [5] fare better on average but are acknowledged, particularly in [1], to still struggle with specific material types such as plastic, and none of the reviewed classification systems describe a confidence threshold below which an item is flagged for human review rather than sorted automatically and silently.
- **Absence of combined segregation-and-logistics visualization.** Bin-level classification ([1], [2], [4], [5]) and route optimization ([6]) are demonstrated separately; none of the reviewed works route a collection truck differently based on whether a bin's contents are actually clean or contaminated. This split means a truck may be dispatched with equal urgency to a bin full of correctly sorted recyclables and one full of commingled waste, reintroducing exactly the kind of undifferentiated handling that bin-level segregation was meant to prevent from ever reaching the truck.
- **Limited adaptability to waste-generation volatility.** The routing model in [6] is built primarily around fill-level trends, with no described mechanism for anticipating a festival, seasonal event, or sudden local surge in waste generation that would shift bins from empty to overflowing far faster than a historical pattern predicts. None of

the reviewed systems describe a retraining or online-adaptation strategy that would let a fill-level or classification model recover quickly once real conditions diverge from the data it was trained or calibrated on.

- **High per-bin hardware and calibration overhead.** The multi-sensor and camera-equipped bins in [1], [4], [5], and [7] each require a non-trivial combination of compute, connectivity, and mechanical actuation per unit, and none of the reviewed works discuss how classification accuracy is maintained as camera angles drift, sensors degrade, or bin placements change across a deployment of thousands of units—a barrier to fast, low-cost, city-wide rollout beyond a single pilot installation.
- **No feedback loop between automated correction and citizen behavior.** The gamified application in [8] rewards a resident for the act of disposing of an item, but has no way to know whether that item was actually sorted correctly, while the bin-level systems in [1], [2], [4], [5], and [7] that do know whether an item was sorted correctly have no channel back to the resident who sorted it. This means that even when a smart bin silently corrects a citizen's mistake, that mistake is never surfaced to the citizen, and the behavioral opportunity to prevent it next time is lost.

PROBLEM STATEMENT

A. Operational Challenges in Municipal Waste Segregation

Three recurring obstacles surface across the literature considered here. The first is the labor intensity and health hazard of manual sorting: someone must physically handle unsorted waste, whether a resident at a kitchen bin or a sanitation worker at a collection point, and this repeated contact carries a real risk of injury and disease transmission that a resident's schedule and a worker's shift pattern are not designed to sustain indefinitely. The second is the purely reactive nature of contamination detection—by design, most systems identify a sorting error only after materials have already been placed together in the same bin or truck, leaving little room for a corrective nudge at the moment the mistake is made. The third is the disconnect between bin-level sensing data and downstream collection logistics: even where a bin can detect that it is full or contaminated, that signal rarely reaches the routing decision that determines when a truck actually arrives to empty it.

These three obstacles tend to compound rather than operate independently. A household that receives no immediate feedback on its sorting mistakes has no practical way to learn from them before the next collection cycle, which means the same category of error can repeat indefinitely across an entire neighborhood. Even where a municipality has already invested in sensor-instrumented bins, that investment rarely closes the loop back to either the resident or the dispatcher: a smart bin that silently logs a contamination event has no direct, real-time way to tell a resident what went wrong or to tell a route planner that this particular bin now needs earlier attention. It is this combination—hazardous manual handling, reactive contamination detection, and a sensing layer disconnected from

both citizen feedback and collection logistics—that any credible automated segregation system has to address together, rather than solving any single piece of it in isolation.

PROPOSED SYSTEM

A. Design Rationale

The gaps identified above motivate a platform built around three coupled capabilities that no single reviewed system combines: cross-validated, edge-deployed classification at the point of disposal; contamination-aware collection routing; and a citizen-facing feedback loop that turns every bin-level correction into an immediate, gamified learning signal for the resident who caused it.

SYSTEM ARCHITECTURE

The proposed platform, referred to here as EcoSort, follows a three-tier architecture. The edge tier consists of a smart bin built around a Raspberry Pi 4 (or ESP32 for lower-cost deployments), a camera module running a lightweight convolutional classifier, and a small sensor suite—an ultrasonic sensor for fill level, an inductive sensor for metal detection, and a moisture sensor used only as a secondary cross-check rather than as the primary classification signal, directly addressing the sensor-fragility gap identified in Section VI. Following the throughput and accuracy trade-offs reported in [1], the on-device model is a MobileNetV3-class network, chosen for its favorable balance of inference speed and accuracy on constrained edge hardware; items are classified into biodegradable, paper, plastic, metal/glass, and hazardous/e-waste categories, and a servo-actuated flap routes each item into the corresponding compartment. Classifications below a confidence threshold are logged as low-confidence rather than acted upon silently, and are queued for periodic human or crowd-sourced verification.

The cloud tier hosts a Python/FastAPI backend and a PostgreSQL database that ingest telemetry from every bin—fill level per compartment, classification counts, contamination flags, and low-confidence images for retraining. A route-optimization module, informed by the variable-neighborhood-search and ant-colony approach validated in [6], combines real-time fill-level data with historical generation patterns to schedule collection dynamically; unlike the reviewed routing literature, this module also ingests each bin's contamination-flag rate, so that a bin reporting frequent low-confidence or cross-check disagreements is prioritized for earlier collection and physical inspection rather than being treated identically to a clean, well-sorted bin. A data-quality watchdog service continuously monitors classification-confidence trends per bin to catch camera drift or sensor degradation before it silently corrupts citywide recycling-stream statistics.


The citizen tier consists of a mobile application through which a resident scans a QR or NFC tag on the bin at the moment of disposal, earning points for a successful, correctly classified deposit; when the edge classifier disagrees with the category the resident selected in the app, the discrepancy is surfaced back to the resident immediately as a short, non-

punitive correction, directly closing the feedback-loop gap identified in Section VI. Points are redeemable for local rewards and displayed on a neighborhood leaderboard, following the point-and-reward mechanics validated in [8]. A parallel municipal dashboard, built with React.js, renders a live, color-coded city map showing each bin's fill level and contamination-flag status, with the optimizer's recommended collection route overlaid directly on the same map—closing the gap noted in Section VI between bin-level sensing and collection logistics, so that a dispatcher sees exactly which bins need attention and why, rather than reading two disconnected reports.


A. Proposed Architecture

- Architecture diagram – for the Proposed Architecture slide.
- AI smart bin photo – to show automatic waste identification.
- Automatic sorting machine – to show the segregation mechanism.
- IoT smart bin – to show sensors and cloud monitoring.

a)



b)




METHODOLOGY/WORKFLOW

A. Operational Flow

A typical interaction begins when a resident approaches an EcoSort bin and scans the bin's QR code in the mobile app before depositing an item. The edge classifier identifies the item, actuates the correct compartment, and returns its classification to the app in real time; if the classifier's category differs from what the resident indicated, the app shows a brief correction rather than deducting points outright, preserving the reward's positive framing while still teaching the resident. The bin's telemetry—updated fill level, the new classification count, and any low-confidence flag—is pushed to the cloud backend, where the data-quality watchdog and route-optimization module update their respective models. The municipal dashboard reflects the updated bin status and, where relevant, an updated recommended route, and sanitation crews receive route updates through the same mobile

platform used by residents, closing the loop from a single point-of-disposal event to a concrete operational and behavioral outcome.



IMPLEMENTATION AND EVALUATION

A. Expected Impact

Taken together, the cross-validated edge classification, the contamination-aware routing layer, and the citizen feedback loop are intended to shift the point at which most sorting errors are caught from a material-recovery facility, where an entire truckload can be disqualified, back to the moment of disposal, where a single item can be corrected at negligible cost. Where a manual or single-sensor system might only ever detect a persistent sorting mistake once it shows up in aggregate contamination statistics weeks later, a resident-facing correction delivered at the bin itself gives that resident an immediate, low-stakes opportunity to learn the right category before their next visit. Over time, this shift from reactive, facility-level contamination detection to point-of-disposal correction is expected to increase the share of collected material that is actually eligible for recycling, reduce unnecessary collection trips to bins that are full of already-clean recyclables, and give municipalities a single operational view—spanning resident behavior, bin-level sensing, and truck routing—that would otherwise require stitching together several unrelated systems.

CONCLUSION

The literature reviewed here shows steady, independent progress on the individual pieces of smart waste segregation—computer-vision classification, sensor-driven bin hardware, fill-level-aware route optimization, and gamified citizen engagement—but no single existing system combines cross-validated point-of-disposal classification,

contamination-aware collection logistics, and a resident-facing behavioral feedback loop into one coherent platform. Each capability has so far been demonstrated in isolation, by a different team, against a different dataset or pilot site, and under different assumptions about connectivity, hardware cost, and citizen participation, which makes it difficult for a municipality to adopt more than one capability at a time without stitching together several unrelated tools. The Intelligent Smart Waste Segregation and Recycling System proposed here, EcoSort, is designed specifically to close that combination gap. An edge-deployed classification layer sorts waste at the point of disposal, cross-checking sensor modalities against each other and flagging low-confidence classifications for review rather than acting on them silently, addressing the sensor-fragility weakness identified as a recurring limitation across the reviewed literature. A contamination-aware routing layer, built on validated route-optimization techniques, prioritizes collection based on what is actually inside a bin rather than fill level alone. A gamified resident application turns every point-of-disposal correction into an immediate, low-stakes learning signal rather than a silently logged statistic, directly addressing the absence of a citizen feedback loop noted as a central research gap in Section

In doing so, the platform aims to shift municipal waste operations away from reactive, facility-level contamination detection and toward proactive, point-of-disposal correction reducing landfill-bound recyclable material, lowering collection costs, and giving municipalities of any size a scalable route to a genuinely closed-loop recycling program. Future extensions of this work could incorporate multilingual voice interaction for residents with limited literacy or smartphone access, extend the classification model to finer-grained recyclable sub-categories, and validate the platform's contamination-reduction impact against real municipal collection data over a full seasonal cycle, further narrowing the gap between the architecture proposed here and a fully field-tested deployment.

REFERENCES

- [1] N. Almtireen, A. A. Abuhejleh, M. Ryalat, H. Elmoaqet, and G. Al-refai, "Deep transfer learning for sustainable waste management: Real-time waste segregation apparatus using a two-phase CNN framework," *J. Supercomput.*, vol. 81, art. 1411, Oct. 2025, doi: 10.1007/s11227-025-07931-2.
- [2] C. P. Mallikarjuna Gowda, S. Yadav, A. Shanmugam, V. Hima, and N. Suresh, "Waste classification and segregation: Machine learning and IOT approach," in *Proc. 2021 2nd Int. Conf. Intelligent Engineering and Management (ICIEM)*, London, U.K., 2021, pp. 233–238, doi: 10.1109/ICIEM51511.2021.9445289.
- [3] M. P. Arthur, S. Shoba, and A. Pandey, "A survey of smart dustbin systems using the IoT and deep learning," *Artif. Intell. Rev.*, vol. 57, no. 3, art. 56, Feb. 2024, doi: 10.1007/s10462-023-10646-6.

- [4] N. Shamin, P. M. Fathimal, R. Raghavendran, and K. Prakash, "Smart garbage segregation & management system using Internet of Things (IoT) & machine learning (ML)," in Proc. IEEE Conf. (IEEE Xplore Document 8741443), 2019.
- [5] K. O. Mohammed Aarif, C. Mohamed Yousuff, B. A. Mohammed Hashim, C. Mohamed Hashim, and P. Sivakumar, "Smart bin: Waste segregation system using deep learning-Internet of Things for sustainable smart cities," *Concurrency Computat.: Pract. Exper.*, vol. 34, no. 28, art. e7378, 2022, doi: 10.1002/cpe.7378.
- [6] A. Roy, A. Manna, J. Kim, and I. Moon, "IoT-based smart bin allocation and vehicle routing in solid waste management: A case study in South Korea," *Comput. Ind. Eng.*, vol. 171, art. 108457, 2022.
- [7] A. Alourani, M. U. Ashraf, and M. Aloraini, "Smart waste management and classification system using advanced IoT and AI technologies," *PeerJ Comput. Sci.*, vol. 11, art. e2777, Apr. 2025, doi: 10.7717/peerj-cs.2777.
- [8] L. Aguiar-Castillo, J. Rufo-Torres, P. De Saá-Pérez, and R. Pérez-Jiménez, "How to encourage recycling behaviour? The case of WasteApp: A gamified mobile application," *Sustainability*, vol. 10, no. 5, art. 1544, 2018, doi: 10.3390/su10051544